

# CONFIX™ WST split cable protection conduits

for cables with connectors



RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

The CONFIX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. [KVT-W90](#), a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of [split grommets](#) offered.

The length of the CONFIX™ WST split corrugated conduit can be customized to your application.

## Defining your individual length:

Order numbers (ex.):

Length = 1.500 mm --> Order No. 31200.01500

**All conduits are available by the metre (0.5 m steps).**

## Specifications

<b>Material</b>	Polypropylene
<b>Operating temperature</b>	-40 C° to 105 C°
<b>Properties</b>	UV-resistant

## Advantages & benefits

■ Retrofits, repairs and maintenance can be done much more easily and quickly

## Product types & sizes

CONFIX™ WST NW 10



Part No.	<b>31200.xxxxx</b>
EAN	
Package quantity	<b>1</b>
Nominal size	<b>NW 10</b>
External diameter	<b>13,6 mm</b>
Internal diameter	<b>8,7 mm</b>
Bending radius (static)	<b>25 mm</b>

**CONFIX™ WST NW 14**



Part No. **31210.xxxxx** Compatible with CONFiX **31410,**  
EAN **31411**  
Package quantity **1** FWS  
Nominal size **NW 14**  
External diameter **18,5 mm**  
Internal diameter **12,5 mm**  
Bending radius **35 mm**  
(static)

**CONFIX™ WST NW 16**



Part No. **31215.xxxxx** Compatible with CONFiX **31413,**  
EAN **31414**  
Package quantity **1** FWS  
Nominal size **NW 16**  
External diameter **21,5 mm**  
Internal diameter **16 mm**  
Bending radius **40 mm**  
(static)

**CONFIX™ WST NW 20**

Part No. **31220.xxxxx**  
EAN  
Package **1**  
quantity  
Nominal size **NW 20**  
External diameter **25,5 mm**  
Internal diameter **19,5 mm**  
Bending radius **45 mm**  
(static)



**CONFIX™ WST NW 23**

Part No. **31230.xxxxx** Compatible with CONFIX **31416,**  
EAN **31417**  
Package **1** FWS  
quantity  
Nominal size **NW 23**  
External diameter **31 mm**  
Internal diameter **24,2 mm**  
Bending radius **50 mm**  
(static)



**CONFiX™ WST NW 29**



Part No. **31235.xxxxx** Compatible with CONFiX **31419, 31420**  
EAN  
Package quantity **1** FWS  
Nominal size **NW 29**  
External diameter **35,5 mm**  
Internal diameter **27,3 mm**  
Bending radius **90 mm**  
(static)

**CONFiX™ WST NW 37**



Part No. **31240.xxxxx** Compatible with CONFiX **31422, 31423**  
EAN  
Package quantity **1** FWS  
Nominal size **NW 37**  
External diameter **41,4 mm**  
Internal diameter **31 mm**  
Bending radius **110 mm**  
(static)

**CONFIX™ WST NW 45**

Part No.	<b>31250.xxxxx</b>	Compatible	<b>31425,</b>
EAN		with CONFIX	<b>31426</b>
Package	<b>1</b>	FWS	
quantity			
Nominal size	<b>NW 45</b>		
External diameter	<b>54 mm</b>		
Internal diameter	<b>42,7 mm</b>		
Bending radius	<b>130 mm</b>		
(static)			



**CONFIX™ WST NW 70**

Part No.	<b>31260.xxxxx</b>		
EAN			
Package	<b>1</b>		
quantity			
Nominal size	<b>NW 70</b>		
External diameter	<b>79,8 mm</b>		
Internal diameter	<b>66,5 mm</b>		
Bending radius	<b>190 mm</b>		
(static)			



