

KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

Black KT-DPF grommets have an increased chemical resistance, e.g. against aggressive oils, coolants etc.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

Cutting of KT-DPF grommets: Cable diameter less 20%. It is recommended that additional strain relief be provided for the cables using a cable tie.

IP54

RIFA

ECOLAB
certified



RoHS
compliant



Made in
Germany


Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	higher chemical resistance


Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes

KT-DPF-A bk  IP54	Part No.	41360	Height	50 mm
	EAN	4251269307102	Mounting height	33 mm
	Package quantity	10	Clamping range	1 x 3 - 12 mm
	For max. no. of cables	1		
	Colour	black		
	Length	21 mm		
	Width	21 mm		

KT-DPF-B bk  IP54	Part No.	41361	Height	59 mm
	EAN	4251269307119	Mounting height	42 mm
	Package quantity	10	For cable type	Round cable
	For max. no. of cables	1	Clamping range	1 x 4 - 18 mm
	Colour	black		
	Length	41,5 mm		
	Width	42 mm		



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41362
4251269307126
10
1
black
41,5 mm
42 mm

Height
Mounting height
For cable type
Clamping range

59 mm
42 mm
Round cable
1 x 14 - 26 mm

icotek[®]
smart cable management